



Built for **Business**

Intuitive A4 Desktop Scanning for Your Business' Hassle-free Operation

As businesses navigate the challenges of the modern world, the imageFORMULA DR-S250N offers the ideal solution for your scanning needs. Elevate your efficiency, minimize physical contact, and stay at the forefront of the evolving work landscape with our forward-looking scanner.

UP TO
50 PPM | **100 IPM*** | **UP TO 1,200 DPI**
FAST SCAN SPEED
SCAN OUTPUT RESOLUTION

*300 dpi, Grayscale, A4



SCAN UP
TO A2*

*With Folio scan,
Long Document mode



ETHERNET

CaptureOnTouch ^{Life}
Web
SCAN VIA
WEB BROWSER

FAST AND HIGH-QUALITY SCANNING

The DR-S250N scanner not only ensures exceptional image quality but also operates at rapid capture speeds, effectively boosting productivity and instilling confidence in all your scanning tasks.



END POINT DIRECT SCANNING

Pre-register frequently used scan and send settings on the scanner to facilitate seamless scanning directly to e-mail, shared folder, printer, FTP, FTPS and SFTP; eliminating the need for computers and/or smart devices.



USE RIGHT OUT OF THE BOX

With CaptureOnTouch Lite Web, complete your scanning tasks using web browsers without the need for driver and software installations. This enables easy sharing of the scanner among multiple users.



SPECIFICATION / DR-S250N

SCAN		
Type		Desktop Sheet-fed Scanner
Scanning Speed ^{*1}	Greyscale	200 dpi: 50 ppm (Simplex) / 100 ipm (Duplex) 300 dpi: 50 ppm (Simplex) / 100 ipm (Duplex)
	Colour	200 dpi: 50 ppm (Simplex) / 100 ipm (Duplex) 300 dpi: 40 ppm (Simplex) / 80 ipm (Duplex)
Scanning Element		Contact Image Sensor (CIS)
Light Source		LED
Scanning Side		Simplex / Duplex
Scanning Modes		Black and White, Greyscale, Colour, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II, Active Threshold
Scanner Features		Double-feed Detection, Folio Scanning, Moiré Reduction, MultiStream, 2D / Barcode
Optical Resolution (Max.)		600 dpi
Output Resolution ^{*2}		100, 150, 200, 240, 300, 400, 600, 1200 dpi
MEDIA HANDLING		
Document Size	Plain Paper	Width: 50.8 to 216 mm Length: 54 to 356 mm (Up to 5,588 mm long with Long Document mode)
	Business Card	Width: 50 to 55 mm Length: 85 to 91 mm
	Card (ISO Standard)	54 x 86 mm
Document Thickness and Weight	Plain Paper	Page Separation: 27 to 209 g/m ² (0.04 to 0.25 mm) Non-separation: 27 to 255 g/m ² (0.04 to 0.3 mm)
	Business Card	128 to 255 g/m ² (0.15 to 0.30 mm)
	Card	1.4 mm or smaller
Auto Document Feeder (ADF) Capacity ^{*3}		60 sheets
CONNECTIVITY & SOFTWARE		
Interface		USB 3.2 / 2.0, 10Base-T/100Base-TX/1000Base-T
Software		ISIS / TWAIN Drivers, CaptureOnTouch
GENERAL		
Power Requirements		AC 100 - 240 V (50 / 60 Hz)
Power Consumption	Scanning (Max.)	22 W
	Sleep Mode	1.6 W
	OFF (Max.)	0.1 W
Operating Environment	Temperature	10 to 32.5°C
	Humidity	20 to 80% RH
Dimensions (W x D x H)	Trays (Closed)	291 x 267 x 242 mm
	Trays (Extended)	291 x 600 x 378 mm
Weight (Approx.)		3.4 kg (Without AC adapter)
CONSUMABLES & ACCESSORIES		
Options / Consumables		Exchange Roller Kit, Carrier Sheet (Passport), Carrier Sheet (A4)
Accessories		Flatbed Scanner Unit 102

Specifications are subject to change without notice.

^{*1} Based on A4 portrait document size.

^{*2} Primary scan lines x secondary scan lines.

^{*3} Size: A4 or smaller, paper weight: 80 g/m².



**SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.**

438A Alexandra Road, #06-10, Alexandra Technopark, Singapore 119967
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.